

# High-Pressure-Cleaner

Hot water, mobile - Series HDE

HDE840-F 24 kW – food appliance, hot water resistant



Gerätetyp		HDE840-F 24kW-Standard	HDE840-F 24kW-Premium
Voltage	3/400-415V/ 50Hz	<ul style="list-style-type: none"> <li>▶ Etronic II - Controls</li> <li>▶ 10m HP-Hose DN08 - 315bar blue</li> <li>▶ Trigger-Gun with swivel</li> <li>▶ Double Spray-Lance 900mm c/w Nozzle-Protection</li> <li>▶ Stainless-Steel Jet-Nozzle 25°</li> <li>▶ Water-Supply separation acc. water reg.</li> <li>▶ Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>	<ul style="list-style-type: none"> <li>▶ Etronic II - Controls</li> <li>▶ Hose-Reel</li> <li>▶ 20m HP-Hose DN08 - 315bar blue</li> <li>▶ Trigger-Gun with swivel</li> <li>▶ Double Spray-Lance 900mm c/w Nozzle-Protection</li> <li>▶ Stainless-Steel Jet-Nozzle 25°</li> <li>▶ Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>▶ Water-Supply separation acc. water reg.</li> <li>▶ Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Operating pressure	30-140bar/ 3-14MPa		
Max. pressure	160bar/ 16MPa		
Discharge capacity	300 - 720l/h		
Nozzle size	045		
Heating capacity	24kW		
Hot water capacity	30 - 80°C		
Pump speed	1400U/min		
Connected load	28,8kW / 44,A		
Electrical protection	3x50A träge		
Weight net / with package		124 kg / 145 kg	133 kg / 154 kg
Dimensions device / with package (LxWxH)		1070 x 735 x 785 mm / 1160 x 770 x 960 mm	1070 x 735 x 1310 mm / 1160 x 770 x 1350 mm
<p>Food appliance with abrasion resistant high pressure hose blue, self-supporting, robust, corrossions free, rotation-moulded device-chassis for food industry, stainless steel, impact-resistant device-cover made of ABS, stainless-steel hotwater-boiler with 65l capacity with pre-heating and buffer storage for immediate hot-water use and hot-water preparation during stand-by operation. Triplex-piston pump with chrome nickel pump head (hot-water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (start-stop system with switch-off delay, stand-by system for heating, low-water cut-off), unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, 2 integrated detergent-tank with 20l capacity, 2-stage rotary on-off switch with stand-by function, 7,5m connection cable, removable ergonomic drawbar stainless steel</p>			
Artikel-Nr.		108003	108004
UVP zzgl. MwSt.		5.949,00 €	6.289,00 €