

High-Pressure-Cleaner

Cold water, mobile - Series 4x4

KD1340



| Type | KD1340-Standard | KD1340-Premium |
|--|--|---|
| Voltage | 3/400-415V/ 50Hz | |
| Operating pressure | 30-170bar/ 3-17MPa | |
| Max. pressure | 190bar/ 19MPa | |
| Discharge capacity | 300 - 1.300l/h | |
| Nozzle size | 070 | |
| Max. Inlet temperature | 45°C | |
| Pump speed | 1400rpm | |
| Connected load | 7,4kW / 13,1A | |
| Electrical protection | 3x16A slow-blowing | |
| Weight net / with package | 89 kg / 113 kg | 97 kg / 121 kg |
| Dimensions device / with package (LxWxH) | 980 x 620 x 1000 mm / 1050 x 760 x 1180 mm | 1020 x 620 x 1000 mm / 1050 x 760 x 1180 mm |

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar

| | | |
|-----------------------|------------|------------|
| Art. No. | 552001 | 552002 |
| Retail price plus VAT | 1.659,00 € | 1.989,00 € |