High Pressure Cleaner



Cold water, stationary - Series KSM KSM3640- hot water resistant















Туре		KSM3640	KSM3640-INOX
Voltage	3/400-415V/ 50Hz	► 7" Touch-Screen Monitor	► Stainless Steel (Food-Safe)
Operating pressure	30-180bar/ 3-18MPa	 PLC Controls Siemens S7-1200 Automatic Switch On and Off Control for high-pressure pumps Automatic Stand-By Operation Pressureless pipes in Stand-By Booster-Supply-Pump 60l Water-Storage tank Water-Supply separation acc. water reg. Maintenance interval display 	 7" Touch-Screen Monitor PLC Controls Siemens S7-1200 Automatic Switch On and Off Control for high-pressure pumps Automatic Stand-By Operation Pressureless pipes in Stand-By Booster-Supply-Pump 60l Water-Storage tank Water-Supply separation acc. water reg. Maintenance interval display
Max. pressure	200bar/ 20MPa		
Discharge capacity	900 - 3600l/h		
Nozzle size	4 x 050		
Max. Inlet temperature	80°C		
Pump speed	1400rpm		
Connected load	27,0kW /50A		
Electrical protection	3x63A slow-blowing		
Weight net / with package		_	_
Dimensions device / with package (LxWxH)		2130 x 800 x 2090 mm /-	2130 x 800 x 2090 mm/-

Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless-steel), suitable for floor installation, triplex-piston pump with chrome-nickel pump head, hot-water resistant up to 85°c, high-performance ceramic piston, stainless-steel valves, leakage-return, booster-pump for charging the high-pressure pumps (cavitation avoidance), automatic pump-on and shut-off control by plc, total-switch-off between 5 to 600min - adjustable, with leakage-recognition, unloader safety-valve for monitoring, pressureless pipe-system in stand-by mode, robust rotary on-off switch - lockable

Art. No.	1563	156300
Retail price plus VAT	17.900,00 €	21.520,00 €